



## GENERAL HANGING INSTRUCTIONS

INSPECT YOUR WALLCOVERING FOR DEFECTS PRIOR TO INSTALLATION. NO CLAIMS WILL BE HONORED AFTER MERCHANDISE HAS BEEN CUT OR HUNG.

### WALL PREPARATION

1. Remove old wallcovering and glue if applicable
2. Wash walls to remove old paste and other foreign matter.
3. Repair wall imperfections with plaster and sand smooth,
4. Wash walls with a strong solution of household bleach to kill mold spores and prevent mildew from occurring.
5. Prime surface to be wallpapered with a white alkyd base primer sold in your local paint & wallpaper stores. DO NOT USE GLUE-SIZE.

### INSTALLATION

#### I TRIMMING

- A. Refer to join marks on paper edge for pattern match (half drop/straight match).
- B. Use trim marks provided to trim excess from edges of paper.

#### II PASTING

- A. This stain-resistant strippable wallcovering can be hung BEST with a clear premixed adhesive. Apply paste generously to the back, edge to edge, smoothly and evenly.
- B. For ease in hanging, we recommend after pasting the complete sheet, that it can be "booked" (folded back to back) and allowed to soak and relax while you proceed to paste sheet #2. After the second sheet is pasted and "booked" - then the first sheet can be applied to the wall.

#### III HANGING

- A. After cutting the desired length and pasting, position the wallcovering on the wall. Use a smoothing brush to remove all air pockets, wrinkles and excess paste by brushing the wallcovering from the center to the edges.
- B. All edges must be rolled down with a seam roller.
- C. Repeat the procedure with the second strip, sliding it into position with its edge butted up against the edge of the proceeding strip. Be sure to match up the design. Do not overlap the wallcovering.
- D. Wash any glue residue from surrounding wood trim/molding immediately upon hanging each panel.

**WASH ADHESIVE COMPLETELY FROM THE SURFACE OF THE WALLCOVERING IMMEDIATELY AFTER EACH STRIP IS HUNG. ANY ADHESIVE LEFT ON THE WALLCOVERING CAN, AT A LATER DATE, ATTACK THE SURFACE PRINTED INKS AND CAUSE THEM TO FLAKE.**

**NOTE:** The highest quality of workmanship is employed in the production of the wallcovering. Careful inspection is made before shipment, however, final inspection and approval are the ultimate responsibilities of the customer. Correct design, color and quantity should be verified before the wallcovering is cut or hung.

